


# HMEX Frame

Standard HMX frame extended using a 10mm thick welded collar. For use in corrugated bulkhead or to fit the frame above deck level.

## CHARACTERISTICS

- Available in four standard sizes with 120mm width (internal), 2,4,6,8. Multiple frames are available as combination of two or more apertures arranged horizontally, vertically or both combined.
- Designed to be welded onto a bulkhead or deck.
- Materials: Mild Steel, Stainless Steel. Other materials under request.
- To be sealed with standard or EMC HF blocks, compression systems and accessories.
- Ex available under request.



HMEX MxN  
HMEX 6x2

HMEX M+P  
HMEX 6+6

HMEX M+PxN  
HMEX 6+6x2

\*Frame designation: M = size row 1; P = size row 2; N = number of columns.

DESCRIPTION	EXTERNAL DIMENSIONS (mm)				WEIGHT (Kg)	
	W	H	Wi	Hi	Mild Steel	Stainless Steel
HMEX 2	160	141	140	121	5,5	5,7
HMEX 2x2	291	141	271	121	8,9	9,1
HMEX 2x3	421	141	401	121	12,2	12,5
HMEX 2x4	551	141	531	121	15,5	15,9
HMEX 2x5	682	141	662	121	18,8	19,3
HMEX 2x6	812	141	792	121	22,2	22,7
HMEX 4	160	199,5	140	179,5	6,8	7,0
HMEX 4x2	291	199,5	271	179,5	10,4	10,7
HMEX 4x3	421	199,5	401	179,5	14,0	14,4
HMEX 4x4	551	199,5	531	179,5	17,6	18,0
HMEX 4x5	682	199,5	662	179,5	21,2	21,7
HMEX 4x6	812	199,5	792	179,5	24,8	25,4


\*All dimensions are nominal values

# HMEX Frame

DESCRIPTION	EXTERNAL DIMENSIONS (mm)				WEIGHT (Kg)	
	W	H	Wi	Hi	Mild Steel	Stainless Steel
HMEX 4+4	160	369	140	349	11,3	11,6
HMEX 4+4x2	291	379	271	359	17,6	18,1
HMEX 4+4x3	421	379	401	359	23,2	23,8
HMEX 4+4x4	551	379	531	359	28,8	29,5
HMEX 4+4x5	682	379	662	359	34,4	35,2
HMEX 4+4x6	812	379	792	359	39,9	40,9
HMEX 6	160	258	140	238	8,1	8,3
HMEX 6x2	291	258	271	238	12,0	12,3
HMEX 6x3	421	258	401	238	15,8	16,2
HMEX 6x4	551	258	531	238	19,7	20,2
HMEX 6x5	682	258	662	238	23,6	24,2
HMEX 6x6	812	258	792	238	27,5	28,2
HMEX 6+6	160	486	140	466	13,8	14,2
HMEX 6+6x2	291	496	271	476	20,8	21,3
HMEX 6+6x3	421	496	401	476	26,9	27,5
HMEX 6+6x4	551	496	531	476	33,0	33,8
HMEX 6+6x5	682	496	662	476	39,1	40,1
HMEX 6+6x6	812	496	792	476	45,2	46,4
HMEX 8	160	316,5	140	296,5	9,4	9,6
HMEX 8x2	291	316,5	271	296,5	13,5	13,9
HMEX 8x3	421	316,5	401	296,5	17,7	18,1
HMEX 8x4	551	316,5	531	296,5	21,8	22,4
HMEX 8x5	682	316,5	662	296,5	26,0	26,6
HMEX 8x6	812	316,5	792	296,5	30,1	30,9
HMEX 8+8	160	603	140	583	16,4	16,8
HMEX 8+8x2	291	613	271	593	23,9	24,5
HMEX 8+8x3	421	613	401	593	30,5	31,3
HMEX 8+8x4	551	613	531	593	37,2	38,1
HMEX 8+8x5	682	613	662	593	43,9	45,0
HMEX 8+8x6	812	613	792	593	50,6	51,8

\*For other sizes or frame combinations not presented here, contact sales department

\*All dimensions are nominal values



→ Installation references

See assembly parts	69
See accessories	79
See installation guide	127
See welding instructions	164
See inspection check	172