

# ◆→ TOLERANT BLOCKS

Hawke HF EMC tolerant blocks are designed to accommodate different cables passing through the frame.


Its special design with five contact points allows the blocks to accommodate different diameters within the same block and accept variances in cable/pipe diameters.

Silver-loaded paint and copper strip wrapping ensures correct shielding.



## CHARACTERISTICS

- ◆ Made of zero halogen, intumescent elastomeric polymer.
- ◆ No modification of the block needed during installation. Zero waste.
- ◆ Sealing grooves in the internal faces ensures correct contact all along your cable.



DESCRIPTION	L (mm)	CABLE AND PIPE DIAMETER		WEIGHT (kg)
		LABEL A MINIMUM (mm)	LABEL B MAXIMUM (mm)	
HF153/E	15	3	5	0,02
HF155/E	15	5	7	0,02
HF157/E	15	7	9	0,01
HF203/E	20	3	6	0,03
HF206/E	20	6	9	0,03
HF209/E	20	9	12	0,03
HF2011/E	20	11	14	0,02
HF2013/E	20	13	16	0,02
HF3012/E	30	12	15	0,05
HF3015/E	30	15	18	0,06
HF3018/E	30	18	21	0,05
HF3021/E	30	21	24	0,04
HF4012/E	40	12	15	0,12
HF4015/E	40	15	18	0,12
HF4022/E	40	22	25	0,10
HF4025/E	40	25	28	0,09
HF4028/E	40	28	31	0,08

## → TOLERANT BLOCKS

DESCRIPTION	L (mm)	CABLE AND PIPE DIAMETER		WEIGHT (kg)	COLOUR
		LABEL A	LABEL B		
		MINIMUM (mm)	MAXIMUM (mm)		
HF4031	40	31	34	0,07	Orange
HF6031	60	31	34	0,22	Red
HF6034	60	34	37	0,21	White
HF6037	60	37	40	0,20	Blue
HF6040	60	40	43	0,19	Orange
HF6043	60	43	46	0,18	Purple
HF6046	60	46	49	0,16	Yellow
HF6049	60	49	52	0,14	Green
HF6052	60	52	54	0,11	Pink
HF9053	90	53	56	0,46	Red
HF9056	90	56	59	0,44	White
HF9059	90	59	62	0,42	Blue
HF9062	90	62	65	0,40	Orange
HF9065	90	65	68	0,39	Purple
HF9068	90	68	71	0,36	Yellow
HF12072	120	72	75	0,79	Red
HF12075	120	75	78	0,75	White
HF12078	120	78	81	0,71	Blue
HF12081	120	81	84	0,67	Orange
HF12084	120	84	87	0,64	Purple
HF12087	120	87	90	0,61	Yellow
HF12090	120	90	93	0,58	Green
HF12093	120	93	96	0,55	Pink
HF12096	120	96	100	0,52	Brown